



Declaration of Performance

Nr DWU-GEO 8 400/1

PRIVATE LABEL GEO 8 400 / **Eurovent GEO 8 400**

| | |
|---|---|
| 1. Unique identification code of the product type | GEO 8 400/1 |
| 2. Intended use or uses | Moisture insulation in insulated buildings waterproofing of underground elements. |
| 3. Manufacturer | Eurosystem Polska Sp. z o.o. Sp. K. Wiejska 13 46-055 Przywory, Poland VAT PL9372516153 |
| 4. System of AVCP | System 2+ |
| 5. Notified body/ies | PN-EN 13967:2012 Notified certification body: Instytut Techniki Budowlanej, Warszawa, RP (Identification No 1488-CPR-0659/Z |

6. Declared performance

| ESSENTIAL CHARACTERISTICS | USEFUL PROPERTIES | TESTING METHOD |
|---|-------------------------------------|--|
| Reaction to fire | Class F | EN 13501-1 |
| Watertightness | Watertight at 60 kPa | EN 1928:2002 (60kPa) |
| Durability: Watertightness after artificial ageing | Watertight at 60 kPa | EN 1928:2002 po badaniu EN 1296 (70°C/ 12 tyg.) |
| Watertightness after exposure to chemicals | Watertight at 60 kPa | EN 1928:2002 po badaniu EN 1847 (23°C/ 28 dni) |
| Tear resistance | NPD | - |
| Joint strength | NPD | - |
| Impact resistance | NPD | - |
| Maximum stretching strength | MD ≥ 165 N/50mm CMD ≥ 140 N/50mm | EN 12311-2:2013 |
| Elongation at maximum strength | MD ≥ 50 % CMD ≥ 25 % | EN 12311-2:2013 |
| Resistance to static loads | NPD | - |
| Dangerous substances | NPD | - |

7. Product does not contain hazardous substances according with REACH regulation.

The performance of the product identified is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with (UE) No 305/2011, under the sole responsibility of manufacturer identified above.

W imieniu producenta podpisał(-a)

Marcin Świerta
Prezes Zarządu



Przywory, 17.03.2025 r.