



Declaration of Performance

Nr DWU-GEO 8 500

PRIVATE LABEL GEO 8 500 / **Eurovent GEO 8 500**

1. Unique identification code of the product type	GEO 8 500
2. Intended use or uses	Elastic waterproofing products. Plastic-based product for damp-proofing and waterproofing of underground structures, with ventilation and drainage function. Type V; Type T.
3. Manufacturer	Eurosystem Polska Sp. z o.o. Sp. K. Wiejska 13 46-055 Przywory, Polska VAT PL9372516153
4. System of AVCP	System 2+
5. Notified body/ies	PN-EN 13967:2012 Notified certification body 1488 (Building Research Institute, Warsaw, Poland). Certificate of Conformity of the Factory Production Control 1488-CPR-0659/Z

6. Declared performance

ESSENTIAL CHARACTERISTICS	USEFUL PROPERTIES	TESTING METHOD
Reaction to fire	Class F	EN 13501-1
Watertightness	Watertight at 60 kPa	EN 1928:2002 (60kPa)
Durability: Watertightness after artificial ageing	Watertight at 60 kPa	EN 1928:2002 po badaniu EN 1296 (70°C/ 12 tyg.)
Watertightness after exposure to chemicals	Watertight at 60 kPa	EN 1928:2002 po badaniu EN 1847 (23°C/ 28 dni)
Tear resistance	NPD	-
Joint strength	NPD	-
Impact resistance	NPD	-
Maximum stretching strength	MD ≥ 235 N/50 mm CMD 230 N/50mm	EN 12311-2:2013
Elongation at maximum strength	MD ≥ 35 % CMD ≥ 30 %	EN 12311-2:2013
Resistance to static loads	NPD	-
Dangerous substances	NPD	-

7. The performance characteristics of the product specified above are in conformity with the set of declared performance characteristics. This Declaration of Performance is issued in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer

Marcin Świerta
President



Przywory, 17.03.2025 r.