

## TECHNICAL DATA SHEET



### Eurovent **FIX METAL 330/30**

The Eurovent<sup>®</sup> FIX METAL 330/30 snow guard bracket is made of galvanized steel with a TOX connection. It enables the installation of a snow guard on metal roof tiles with a 330 module. Available in several color versions coated with powder paint according to the RAL color palette. Mounted on roof slopes with a pitch from 15° to 60°.

PARAMETER	UNIT	VALUE
Material composition		Steel grade S235JR
Type of roofing		For profiled metal roof tiles
Thickness of paint coating	[µm]	≥ 60
Corrosion protection		Hot-dip galvanized
Thickness of zinc coating	[µm]	≥ 55
Color	[RAL]	brick 8004, brown 8017, brown 8019, anthracite 7016, black 9005, chestnut 3009, cherry 3004
Packaging	[pieces]	5



## Eurovent **FIX METAL 330/30**

**Application:** It is used as a bracket for the Eurovent® SNOWSTOPPER snow guard. Serving as a protective element, it enables the proper fastening of the snow guard on pitched roofs covered with profiled metal roof tiles with a 330 module. The bracket is mounted together with the Eurovent® SNOWSTOPPER snow guard by pressing and bending the fastening element using the “click” technique.

BRACKET	METAL ROOF TILE MODULE LENGTH “M” [mm]	EMBOSSING HEIGHT “H” [mm]
FIX METAL 330/30	330	30

**Installation:** Mounted to the roof covering, i.e. metal roof tiles, as well as under the batten using screws.

**Safety:** The product is not intended for consumption, avoid contact with eyes. In case of skin irritation, consult a doctor.

**Storage / transport:** The product should be stored in dry, covered rooms, free from moisture and direct UV radiation. Under heavy load, the product may deform, warp, or damage the galvanized and painted coating. Therefore, stacking with other heavy products (both during transport and storage) is not recommended. Transport should be carried out in covered vehicles, secured against damage. During transport, transport safety regulations must be observed. The product must be protected against chemical agents, particularly solvent-based substances, as they may reduce its technical parameters or cause permanent damage.

The product is covered by a warranty provided that the guidelines contained in the technical data sheet are strictly followed. The manufacturer reserves the right to refuse warranty claims in case of non-compliance with these guidelines.

*Contained information, advice and guidance is given based on our knowledge, researches, experience and in good faith. We are not responsible for the consequences of improper or incorrect use of our products. Each user of this material will ensure in every possible way, including an examination of the final product in the relevant conditions, the suitability of supplied materials to achieve the objectives pursued by him.*

Product information can be found on the website: [www.eurovent.de](http://www.eurovent.de)

Update date: 13/01/2026