

## TECHNICAL DATA SHEET

### Eurovent **FLEX FLAT PB**



Self-adhesive lead chimney tape used for flashing around chimneys, dormers, and roof windows. It is also applied at roof-to-wall connections. Made of high-quality flat lead sheet and butyl adhesive.

PARAMETER	UNIT	VALUE
Material composition		Lead, butyl
Roll width	[mm]	300
Roll length	[mb]	5
Lead	[mm]	Width: 300 Thickness: 0.12
Butyl		Dimensions: 290 x 1.0 mm Colour: Black Density: 1.65 ± 0.05 g/cm <sup>3</sup> Peel resistance: > 25 (35 ± 10) N/24 mm Solvents: none Ageing resistance of butyl tape: good, also in warm and humid conditions
Colour	[RAL]	Brick red 8004, brown 8019, brown 8017, anthracite 7021, chestnut 8012, black 9005
Application temperature	[°C]	from 5 to 40
Storage period	[month]	to 12
Carton	[pcs.]	1
Pallet	[pcs.]	60



## TECHNICAL DATA SHEET

### Eurovent FLEX FLAT PB

**Application:** Used for all types of sealing and connections within the roof, particularly for chimney flashing, dormers, and roof windows. It is also applied when connecting roof surfaces with walls. Suitable for use on most roofing materials — ceramic and concrete tiles, metal roof tiles, trapezoidal sheets, and profiled aluminium sheets, etc.

**Installation:** For about 24 hours before application, the tape should be stored at room temperature (from 5 °C to 25 °C). The application temperature should be above 5 °C (recommended above 10 °C). The surface to which the tape is applied must be dry and free from dust and grease. Remove the protective liner, place the tape in the desired position, and press firmly.

**Safety:** The product is not intended for consumption. Avoid contact with eyes. In case of skin irritation, consult a doctor.

**Storage / transport:** The product should be stored in dry, covered areas, free from moisture and direct UV radiation. Under heavy load, the product may deform or become damaged. As the product is partly made of flexible lead sheet, it is recommended to store it in its original, sealed packaging. Stacking with other heavy items (both during transport and storage) is not advised. Transport should be carried out in covered vehicles, protected against damage. During transport, applicable transport safety regulations must be observed. The product must be protected from exposure to chemicals, especially solvent-based substances, as these may reduce its technical performance or cause permanent damage.

The product is covered by warranty provided that the guidelines specified in the technical data sheet are strictly followed. The manufacturer reserves the right to reject claims in cases of non-compliance with the given instructions.

*Contained information, advice and guidance is given based on our knowledge, researches, experience and in good faith. We are not responsible for the consequences of improper or incorrect use of our products. Each user of this material will ensure in every possible way, including an examination of the final product in the relevant conditions, the suitability of supplied materials to achieve the objectives pursued by him.*

Product information can be found on the website: [www.eurovent.pl](http://www.eurovent.pl)

Update date: 26/01/2026