

TECHNICAL DATA SHEET

Eurovent **PLATFORM SET DB-DC SHORT**



Eurovent® PLATFORM SET DB-DC SHORT chimney walkway in a complete installation kit consisting of two Eurovent® SUPPORT DB-DC SHORT brackets, two Eurovent® GRIP cradles, a set of mounting bolts, and the Eurovent® PLATFORM chimney walkway. The elements made of galvanized steel form a complete system for safe movement on the roof slope with an inclination from 15° to 60°. The set is available in several powder-coated color versions according to the RAL color chart.

PARAMETER	UNIT	VALUE
Material		Steel grade S235JR
UV resistance		Resistant
Type of roofing		Concrete and ceramic roof tiles
Length	[mm]	0.4; 0.8
Strength of elements	[standard]	EN 516:2007
Anti-slip surface		YES
Corrosion protection		Hot-dip galvanized
Colors	[RAL]	brick 8004, brown 8017, brown 8019, anthracite 7016, graphite 7024, black 9005, cherry 3004, chestnut 3009, cherry 3011
Package weight	[kg]	ca. 6; ca. 7.5
Packaging	[pieces]	1 PLATFORM + 2 GRIP + 2 SUPPORT DB-DC SHORT + 8 screws



Eurovent PLATFORM SET DB-DC SHORT

Application: Eurovent® PLATFORM SET DB-DC SHORT chimney walkway is used as a roof communication element enabling safe and efficient movement of the chimney sweeper in the chimney area. The set includes all components required for platform installation. Thanks to a wide range of brackets, the product can be adapted to almost any type of roof covering. Installation is recommended on roof slopes with an inclination from 15° to 60°.

Installation: The set is mounted directly to the roof structure onto the batten using screws.

Safety: The product is not intended for consumption; avoid contact with eyes. In case of skin irritation, consult a doctor.

Storage / transport: The product should be stored at room temperature in its original packaging, in dry, covered premises free from moisture. Under heavy load, the elements of the set may deform, bend, or suffer damage to the galvanized and painted coating. Therefore, it is recommended not to stack the product with other heavy items (both during transport and storage). It must be transported in covered vehicles, secured against damage. During transport, applicable transport safety regulations must be observed. The product must be protected against chemical agents that could reduce its technical properties or cause permanent damage.

The product is covered by warranty on the condition of strict compliance with the guidelines provided in the technical data sheet. The manufacturer reserves the right to refuse warranty claims in case of non-compliance with the given instructions.

Contained information, advice and guidance is given based on our knowledge, researches, experience and in good faith. We are not responsible for the consequences of improper or incorrect use of our products. Each user of this material will ensure in every possible way, including an examination of the final product in the relevant conditions, the suitability of supplied materials to achieve the objectives pursued by him.

Product information can be found on the website: www.eurovent.de

Update date: 10/09/2025