

## TECHNICAL DATA SHEET

### Eurovent PLATFORM SET METAL 350/20



Eurovent® PLATFORM SET METAL 350/20 chimney walkway in a complete installation set consisting of two Eurovent® SUPPORT DB-DC brackets, two Eurovent® GRIP cradles, a set of mounting screws, and the Eurovent® PLATFORM chimney walkway. The elements made of galvanized steel form a complete system for safe movement on roof slopes with a pitch from 15° to 60°. The set is available in several powder-coated color variants according to the RAL color chart.

PARAMETER	UNIT	VALUE
Material composition		Steel grade S235JR
UV resistance		Durable
Type of roofing		Metal roofing tile with 350 module
Length	[mm]	0,4; 0,8
Element strength	[standard]	EN 516:2007
Anti-slip surface		YES
Corrosion protection		Hot-dip galvanized
Colour	[RAL]	brick 8004, brown 8017, brown 8019, anthracite 7016, graphite 7024, black 9005, cherry 3004, chestnut 3009, cherry 3011
Package weight	[kg]	ca. 5.5; ca. 7
Packaging	[pieces]	1 PLATFORM + 2 GRIP + 2 SUPPORT METAL 350/20 + 8 screws



## Eurovent **PLATFORM SET METAL 350/20**

**Application:** Eurovent<sup>®</sup> PLATFORM SET METAL 350/20 chimney walkway is used as a roof communication element enabling safe and efficient movement of the chimney sweep in the chimney area. The set includes all components necessary for platform installation. Thanks to a wide range of brackets, the product can be adapted to almost any type of roof covering. Installation is recommended on roof slopes with a pitch from 15° to 60°.

**Installation:** The set is mounted directly to the roof structure on the batten using screws.

**Safety:** The product is not intended for consumption, avoid contact with eyes, and in case of skin irritation consult a doctor.

**Storage / transport:** The product should be stored at room temperature, in its original packaging, in dry, covered rooms free from moisture. Under heavy loads, the set components may become deformed, bent, or suffer damage to the zinc and paint coating. Therefore, stacking with other heavy products is not recommended (both during transport and storage). Transport should be carried out in covered vehicles, secured against damage. Transport safety regulations must be observed. The product must be protected against chemical agents that could reduce its technical properties or cause permanent damage.

The product is covered by the warranty provided that the guidelines contained in the technical data sheet are strictly followed. The manufacturer reserves the right to refuse a warranty claim in case of non-compliance with the presented guidelines.

*Contained information, advice and guidance is given based on our knowledge, researches, experience and in good faith. We are not responsible for the consequences of improper or incorrect use of our products. Each user of this material will ensure in every possible way, including an examination of the final product in the relevant conditions, the suitability of supplied materials to achieve the objectives pursued by him.*

Product information can be found on the website: [www.eurovent.de](http://www.eurovent.de)

Update date: 16/09/2025