


TECHNICAL DATA SHEET



Eurovent PRIMER

High-performance primer spray. Used as a preparatory coating before applying adhesive tapes or sealants on loose, absorbent, fibrous, sandy, or otherwise challenging surfaces with low adhesion. It features high coverage efficiency, fast drying time, strong bonding with the substrate, and excellent ageing resistance. The rotating spray nozzle allows for easy and precise application. Suitable for both exterior and interior use in well-ventilated areas.

| PARAMETER | UNIT | VALUE |
|-------------------------|----------|--|
| Material | | Synthetic rubber |
| Cartridge capacity | [ml] | 500 |
| Application temperature | [°C] | -10 to +30 |
| Temperature resistance | [°C] | -20 to + 80 |
| Shelf life | [months] | Min. 12 |
| Waste management | | Do not dispose of in household waste, Do not empty into drains. |
| Color | | Colourless |
| Packaging | [pcs.] | 12 |
| Pallet | [pcs.] | 1008 |



TECHNICAL DATA SHEET

Eurovent PRIMER

Application: Used as a primer before the application of adhesive tapes or sealants on loose, absorbent, fibrous, sandy, or other surfaces with low adhesion.

Assembly: To ensure effective bonding, make sure the surface is firm, dry, clean, and free from dust and grease. Compatibility testing of the materials to be bonded is required. Apply PRIMER evenly to the surface, holding the can at least 20 cm away. Depending on the material used, allow to ventilate for 5–15 minutes. Repeat the process for highly absorbent surfaces. Protect sprayed areas from moisture, dust, and contamination. After each spraying procedure, turn the can upside down and continue spraying until only the propellant is released. This prevents the nozzle from clogging with adhesive residue. Clean any remaining adhesive from the spray nozzle. The valve can be adjusted to three different levels. The spray head can also be rotated between horizontal and vertical spray patterns.

Safety: The product is not intended for consumption. Avoid contact with eyes. In case of skin irritation, consult a physician. Extremely flammable aerosol. Pressurised container. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, and open flames. Do not expose to temperatures exceeding 50 °C. Do not spray towards open flames or other sources of ignition. Do not pierce or burn, even after use. Do not inhale the aerosol. Use only outdoors or in well-ventilated areas. Causes serious eye irritation. May cause drowsiness or dizziness. Harmful to aquatic life with long-lasting effects. In case of ingestion or eye contact, seek medical advice immediately. Avoid direct contact with skin. During use, wear solvent-resistant protective gloves and safety goggles.

Storage / transport: The product should be stored at room temperature in dry, covered areas, free from moisture and direct UV exposure. It must be transported in covered vehicles, properly secured against damage. The product should be protected from chemical agents, especially solvent-based substances, as these may impair its technical properties or cause permanent damage. The product is covered by a warranty, provided that all instructions specified in the technical data sheet are strictly followed. The manufacturer reserves the right to reject any warranty claims resulting from failure to comply with these guidelines.

Contained information, advice and guidance is given based on our knowledge, researches, experience and in good faith. We are not responsible for the consequences of improper or incorrect use of our products. Each user of this material will ensure in every possible way, including an examination of the final product in the relevant conditions, the suitability of supplied materials to achieve the objectives pursued by him.

Product information can be found on the website: www.eurovent.de

Update date: 15/07/2025