

## TECHNICAL DATA SHEET

Eurovent **SNOWSTOP DB**

The snow guard is used as an element that breaks up large amounts of snow sliding down the roof slope towards the eaves. Made entirely of galvanized steel, it is double-coated with polyester paint. Available in several colors according to the RAL palette. Dedicated to a specific group of roofing manufacturers.



PARAMETER	UNIT	VALUE
Material composition		Steel grade S235JR
Dimensions	[mm]	34 x approx. 380
Type of roofing		For cement roof tiles and plain tiles Braas; Euronit; Nelskamp; Koramic; Jopek; IBF; Creton Viva; Rupp Topas;
Steel sheet thickness	[mm]	1,20 - 1,5 (±0,20)
Nose height	[mm]	65
Weight	[kg/pcs.]	approx. 0.21
UV resistance		Resistant
Color	[RAL]	brick 8004; brown 8019; chestnut 8015; black 9005; anthracite 7016; cherry 8012;
Packaging	[pcs.]	100
Pallet	[pcs.]	3 000



## Eurovent **SNOWSTOP DB**

**Application:** Used on pitched roofs as a snow breaker – snow guard. Mounted behind an additional batten or behind individual roof tiles using a specially profiled end. Thanks to its application, large amounts of snow sliding down the roof are broken into smaller pieces and, when falling, do not pose a threat to people near the building.

**Safety:** The product is not intended for consumption, avoid contact with eyes. In case of skin irritation, consult a doctor.

**Storage / transport:** The product should be stored at room temperature, in its original packaging, in dry, covered rooms free from moisture. Under heavy load, the bracket may deform and warp. Therefore, stacking with other heavy products (both during transport and storage) is not recommended. Brackets should be transported in covered vehicles, secured against damage. During transport, transport safety regulations must be observed. The product must be protected against chemical agents that could reduce its technical performance or cause permanent damage.

The product is covered by a warranty provided that the guidelines contained in the technical data sheet are strictly followed. The manufacturer reserves the right to refuse warranty claims in case of non-compliance with these guidelines.

*Contained information, advice and guidance is given based on our knowledge, researches, experience and in good faith. We are not responsible for the consequences of improper or incorrect use of our products. Each user of this material will ensure in every possible way, including an examination of the final product in the relevant conditions, the suitability of supplied materials to achieve the objectives pursued by him.*

Product information can be found on the website: [www.eurovent.de](http://www.eurovent.de)

Update date: 14/01/2026