

TECHNICAL DATA SHEET

Eurovent **SNOWSTOP UNI SHORT**

Eurovent[®] SNOWSTOP UNI SHORT snow guard is used as an element that breaks up large amounts of snow sliding down the roof slope toward the eaves. It is made entirely of galvanized steel and double-sided coated with polyester paint. Available in several colors according to the RAL palette. Designed for a specific group of flat roofing manufacturers.



PARAMETER	UNIT	VALUE
Material composition		Stal gat. S235JR
Dimensions	[mm]	34 x ca. 380
Roof covering type		For roofing felt, bituminous shingles, flat metal sheets
Steel sheet thickness	[mm]	1,20 - 1,5 (±0,20)
Corrosion category	[Norm system 4]	C1; C2; C3;
UV resistance		Resistant
Color	[RAL]	brick red 8004; brown 8019; chestnut 8015; black 9005; anthracite 7016; cherry red 8012;
Packaging	[pieces]	100
Pallet	[pieces]	3 000



Eurovent **SNOWSTOP UNI SHORT**

Application: Eurovent® SNOWSTOP UNI SHORT snow guard is used on pitched roofs as a snow-breaking element. It is installed directly onto the roof decking using screws. Thanks to its use, large amounts of snow sliding off the roof are broken into smaller pieces and, as they slide down, do not pose a hazard to people in the vicinity of the building. It also provides protection against damage to the roof gutter system.

Safety: The product is not intended for consumption. Avoid contact with eyes. In the event of skin irritation, consult a physician.

Storage / transport: The product should be stored at room temperature, in its original packaging, in dry, covered areas free from moisture. Under heavy loads, the bracket may become deformed; therefore, it is recommended not to stack the product with other heavy items, both during transport and storage. The brackets should be transported using covered means of transport and properly secured against damage. Transport safety regulations must be observed during transportation. The product must be protected from exposure to chemicals that could reduce its technical performance or cause permanent damage.

The product is covered by a warranty provided that the guidelines included in the technical data sheet are strictly followed. The manufacturer reserves the right to refuse warranty claims in the event of failure to comply with the specified guidelines.

Contained information, advice and guidance is given based on our knowledge, researches, experience and in good faith. We are not responsible for the consequences of improper or incorrect use of our products. Each user of this material will ensure in every possible way, including an examination of the final product in the relevant conditions, the suitability of supplied materials to achieve the objectives pursued by him.

Product information can be found on the website: www.eurovent.de

Update date: 29/01/2026