

TECHNICAL DATA SHEET

Eurovent **SNOWSTOPPER SET METAL 330/30**



A snow protection system in a complete installation set consisting of the Eurovent[®] SNOWSTOPPER snow guard fence, Eurovent[®] FIX METAL FINNERA brackets adapted to the metal roof tile module, and Eurovent[®] CLIP connectors. The components are made of galvanized steel and provide effective protection against large amounts of snow sliding off the roof slope. The set is available in a galvanized version and in several powder-coated color options according to the RAL palette.

PARAMETER	UNIT	VALUE
Material composition		Steel grade S235JR
Type of roofing		For metal roof tiles with a FINNERA module
Snow guard fence dimensions	[mb]	1,0; 2,0; 3,0;
Paint coating thickness	[μ m]	≥ 60
Corrosion protection		Hot-dip galvanized
Zinc coating thickness	[μ m]	≥ 55
Color	[RAL]	brick 8004, brown 8017, brown 8019, anthracite 7016, black 9005, chestnut 3009, cherry 3004
Packaging	[pieces]	<ul style="list-style-type: none"> - SNOWSTOPPER SET 1,2 m: 1 SNOW-STOPPER 1,2 m + 2 FIX METAL - SNOWSTOPPER SET 2,4 m: 2 SNOW-STOPPER 1,2 m + 4 FIX METAL + 2 CLIP - SNOWSTOPPER SET 3,6 m: 3 SNOW-STOPPER 1,2 m + 6 FIX METAL + 4 CLIP



Eurovent **SNOWSTOPPER SET METAL 330/30**

Application: It is used as a snow protection element preventing large amounts of snow from sliding off roof slopes covered with profiled metal roof tiles. The set can be applied on pitched roofs with a slope from 10° to 90°. Thanks to a wide range of brackets, the product can be adapted to almost any type of metal roof tile with a 350 module. The set is packed in a carton containing all installation components, which significantly reduces installation time and eliminates possible errors during set completion. For lengths of 2.4 m and 3.6 m, the individual elements are connected with special Eurovent[®] CLIP connectors included in the set.

Safety: The product is not intended for consumption. Avoid contact with eyes. In case of skin irritation, consult a doctor.

Storage / transport: The set should be stored at room temperature, in its original packaging, in dry, covered rooms free from moisture. Under heavy load, the components may become deformed or damaged, including the zinc and paint coating. Therefore, it is recommended not to stack the product with other heavy items (both during transport and storage). It should be transported in covered vehicles, protected against damage. Transport safety regulations must be observed. The product should be protected from chemical agents that could reduce its technical properties or cause permanent damage.

The product is covered by a warranty provided that the guidelines contained in the technical data sheet are strictly followed. The manufacturer reserves the right to refuse warranty claims in the event of non-compliance with these guidelines.

Contained information, advice and guidance is given based on our knowledge, researches, experience and in good faith. We are not responsible for the consequences of improper or incorrect use of our products. Each user of this material will ensure in every possible way, including an examination of the final product in the relevant conditions, the suitability of supplied materials to achieve the objectives pursued by him.

Product information can be found on the website: www.eurovent.de

Update date: 14/01/2026