

TECHNICAL DATA SHEET

Eurovent **STEP SET UNI**



Eurovent[®] STEP SET UNI chimney step delivered as a complete installation set consisting of the Eurovent[®] SUPPORT UNI bracket and the Eurovent[®] STEP UNI chimney step. The elements made of galvanized steel are part of a system designed to ensure safe movement on pitched roofs with a slope from 15° to 60°. The step features anti-slip embossing across the entire surface as well as a hand grip. Available in several color versions, powder-coated according to the RAL color palette.

PARAMETER	UNIT	VALUE
Material composition		Steel grade S235JR
Type of roofing		For flat coverings
Step dimensions	[mm]	approx. 160 x 250
Element strength	[Standard]	EN 516:2007
Anti-slip surface		YES
Corrosion protection		Hot-dip galvanized
Color	[RAL]	brick 8004, brown 8017, brown 8019, anthracite 7016, graphite 7024, black 9005, cherry 3004, chestnut 3009, cherry 3011
Packaging	[pieces]	2 STEP + 2 SUPPORT UNI + 4 screws

* on request



Eurovent **STEP SET UNI**

Application: Eurovent[®] STEP SET UNI chimney step is used as a roof communication element, enabling the chimney sweeper to move safely around the chimney area. The set consists of 2 complete steps and includes all elements necessary for the installation of two chimney steps. Thanks to a wide range of brackets, the product can be adapted to almost any type of roofing. Installation is recommended on roof slopes from 15° to 60°.

Installation: The set is mounted directly to the roof structure using an additional counter-batten or directly onto the roof decking with screws.

Safety: The product is not intended for consumption, avoid contact with eyes, and in case of skin irritation consult a doctor.

Storage / transport: The product should be stored at room temperature, in its original packaging, in dry, covered areas free from moisture. Under heavy load, the product may deform, warp, or suffer damage to the galvanized and painted coating. Therefore, it is recommended not to stack the product with other heavy items (both during transport and storage). It should be transported in covered vehicles, secured against damage. During transport, transport safety regulations must be observed. The product must be protected against exposure to chemical agents that could reduce its technical performance or cause permanent damage.

The product is covered by warranty provided that the guidelines contained in the technical data sheet are strictly followed. The manufacturer reserves the right to refuse warranty claims in case of non-compliance with the presented guidelines.

Contained information, advice and guidance is given based on our knowledge, researches, experience and in good faith. We are not responsible for the consequences of improper or incorrect use of our products. Each user of this material will ensure in every possible way, including an examination of the final product in the relevant conditions, the suitability of supplied materials to achieve the objectives pursued by him.

Product information can be found on the website: www.eurovent.de

Update date: 16/09/2025