

## TECHNICAL DATA SHEET



### Eurovent **SUPPORT DB-DC SHORT**

The Eurovent<sup>®</sup> SUPPORT DB-DC SHORT bracket is a mounting element for installing a chimney walkway or a chimney step. Made of hot-dip galvanized steel sheet. It enables the installation of communication elements on pitched roofs covered with concrete or ceramic roof tiles. Supplied as a set with screws, available in a powder-coated version.

| PARAMETER              | UNIT     | VALUE   |
|------------------------|----------|---|
| Material composition   |          | Steel grade S235JR  |
| Type of roofing        |          | For concrete and ceramic roof tiles (with additional sealing foam)  |
| Coating thickness      | [µm]     | ≥ 60  |
| Corrosion protection   |          | Hot-dip galvanized  |
| Zinc coating thickness | [µm]     | ≥ 55  |
| Color                  | [RAL]    | brick 8004, brown 8017, brown 8019, anthracite 7016, graphite 7024, black 9005, cherry 3004, chestnut 3009, cherry 3011 |
| Packaging              | [pieces] | 10  |

\* on request



## Eurovent **SUPPORT DB-DC SHORT**

**Application:** It is used as a roof communication element, enabling efficient installation of the Eurovent<sup>®</sup> PLATFORM chimney walkway or the Eurovent<sup>®</sup> STEP chimney step on roof coverings made of concrete or ceramic roof tiles. When installing the Eurovent<sup>®</sup> PLATFORM chimney walkway, the universal Eurovent<sup>®</sup> GRIP fastener must also be used.

**Installation:** The set is mounted directly to the roof structure with a batten using screws.

**Safety:** The product is not intended for consumption, avoid contact with eyes, and in case of skin irritation consult a doctor.

**Storage / transport:** The product should be stored in dry, covered areas, free from moisture and direct UV radiation. Under heavy load, the product may deform, warp, or suffer damage to the galvanized and painted coating. Therefore, it is recommended not to stack the product with other heavy items (both during transport and storage). It should be transported in covered vehicles, secured against damage. During transport, transport safety regulations must be observed. The product must be protected against exposure to chemical agents, especially solvent-based substances, as they may reduce its technical performance or cause permanent damage.

The product is covered by warranty provided that the guidelines contained in the technical data sheet are strictly followed. The manufacturer reserves the right to refuse warranty claims in case of non-compliance with the presented guidelines.

*Contained information, advice and guidance is given based on our knowledge, researches, experience and in good faith. We are not responsible for the consequences of improper or incorrect use of our products. Each user of this material will ensure in every possible way, including an examination of the final product in the relevant conditions, the suitability of supplied materials to achieve the objectives pursued by him.*

Product information can be found on the website: [www.eurovent.de](http://www.eurovent.de)

Update date: 16/09/2025