

TECHNICAL DATA SHEET



Eurovent **SUPPORT DB-DC WEST EPDM**

Single-piece bracket for the installation of chimney platforms and chimney steps, made of galvanized steel. It is used as an element enabling easy installation of a chimney platform or chimney step on roof coverings. Available in a galvanized version and in several powder-coated color variants according to the RAL color palette.

PARAMETER	UNIT	VALUE
Material composition		Steel grade S235JR
Type of roofing		For concrete and ceramic roof tiles (additional sealing foam)
Paint coating thickness	[µm]	≥ 60
Corrosion protection		Hot-dip galvanized
Zinc coating thickness	[µm]	≥ 55
Color	[RAL]	brick 8004, brown 8017, brown 8019, anthracite 7016, graphite 7024, black 9005, cherry 3004, chestnut 3009, cherry 3011
Packaging	[pieces]	10

* on request



Eurovent **SUPPORT DB-DC WEST EPDM**

Application: It is used as a roof communication element enabling the efficient installation of the Eurovent[®] PLATFORM chimney walkway or the Eurovent[®] STEP chimney step on roof coverings made of concrete or ceramic tiles. When installing the Eurovent[®] PLATFORM chimney walkway, the universal Eurovent[®] GRIP fastener must also be used.

Installation: The installation of brackets does not require an additional batten. The brackets are hooked onto a previously prepared roof tile and the batten on which it is laid. Roof tiles in the areas of contact with the brackets should be prepared by grinding the interlocks. The holes in the hook are used to fasten the bracket to the batten. In the case of concrete roof tiles, the interlock of the covering tile should be ground, while for ceramic roof tiles, the interlocks of both the base tile and the covering tile should be ground.

Safety: The product is not intended for consumption, avoid contact with eyes, in case of skin irritation consult a doctor.

Storage / transport: The product should be stored in dry, covered areas, free from moisture and direct UV radiation. Under heavy load, the product may deform, warp, or suffer damage to the galvanized and painted coating. Therefore, it is recommended not to stack the product with other heavy items (both during transport and storage). It should be transported in covered vehicles, secured against damage. During transport, transport safety regulations must be observed. The product must be protected against exposure to chemical agents, especially solvent-based substances, as they may reduce its technical performance or cause permanent damage.

The product is covered by warranty provided that the guidelines contained in the technical data sheet are strictly followed. The manufacturer reserves the right to refuse warranty claims in case of non-compliance with the presented guidelines.

Contained information, advice and guidance is given based on our knowledge, researches, experience and in good faith. We are not responsible for the consequences of improper or incorrect use of our products. Each user of this material will ensure in every possible way, including an examination of the final product in the relevant conditions, the suitability of supplied materials to achieve the objectives pursued by him.

Product information can be found on the website: www.eurovent.de

Update date: 16/09/2025