

## TECHNICAL DATA SHEET

### Eurovent **SUPPORT METAL 290/30**



Eurovent<sup>®</sup> SUPPORT METAL HYYGGE bracket is a component for installing a chimney walkway holder and a chimney step. Made of hot-dip galvanized steel sheet. The bracket enables the installation of roof communication systems on pitched roofs with a slope from 15° to 60°, covered with roof tiles with a 290/26 mm module, adapted to 290/30 roof tiles. Supplied as a set with screws, in a powder-coated version.

PARAMETER	UNIT	VALUE
Material composition		Steel grade S235JR
Type of roofing		For profiled roof tiles with 290/30 module
UV resistance		Resistant
Coating thickness	[µm]	≥ 60
Corrosion protection		Hot-dip galvanized
Zinc coating thickness	[µm]	≥ 55
Colour	[RAL]	brick 8004, brown 8017, brown 8019, anthracite 7016, graphite 7024, black 9005, cherry 3004, chestnut 3009, cherry 3011
Packaging	[pieces]	10



## Eurovent **SUPPORT METAL 290/30**

**Application:** The Eurovent® SUPPORT METAL 290/30 bracket is used as a roof communication element, enabling the proper installation of the Eurovent® PLATFORM chimney walkway or the Eurovent® STEP chimney step on roof tiles with a 30 mm embossing. When installing the chimney walkway, the universal Eurovent® GRIP holder should additionally be used.

BRACKET	LENGTH OF THE METAL ROOF TILE MODULE "M" [mm]	EMBOSSING HEIGHT "H" [mm]
SUPPORT METAL 290/30	290	30

**Installation:** Mounted to the roof covering, i.e. roof tiles, as well as under the batten using screws.

**Safety:** The product is not intended for consumption, avoid contact with eyes. In case of skin irritation, consult a doctor.

**Storage / transport:** The product should be stored in dry, covered rooms, free from moisture and direct UV radiation. Under heavy load, the product may deform, warp, or suffer damage to the galvanized and painted coating. Therefore, it is recommended not to stack the product with other heavy items (both during transport and storage). Transport should be carried out in covered vehicles, secured against damage. During transport, all transport safety regulations must be observed. The product must be protected from exposure to chemicals, particularly solvent-based substances, as these may reduce its technical performance or cause permanent damage.

The product is covered by warranty provided that the guidelines contained in the technical data sheet are strictly followed. The manufacturer reserves the right to refuse warranty claims in case of non-compliance with these guidelines.

*Contained information, advice and guidance is given based on our knowledge, researches, experience and in good faith. We are not responsible for the consequences of improper or incorrect use of our products. Each user of this material will ensure in every possible way, including an examination of the final product in the relevant conditions, the suitability of supplied materials to achieve the objectives pursued by him.*

Product information can be found on the website: [www.eurovent.de](http://www.eurovent.de)

Update date: 16/09/2025