

TECHNICAL DATA SHEET



Eurovent **TOPBAND**

Eurovent[®] TOPBAND is a single-sided tape designed for bonding and repairing roof membranes and other construction products made of polypropylene. Constructed from polypropylene fleece and coated with an acrylic dispersion adhesive, the tape remains breathable across its entire surface, preserving the vapour permeability of the membrane while providing protection against external moisture and wind.

PARAMETER	UNIT	VALUE
Material		Polypropylene fleece, solvent-free acrylic dispersion adhesive, EC1 ^{plus}
Width	[mm]	50
Length	[mb]	25
Adhesive thickness	[mm]	0,18
Nonwoven thickness	[mm]	0,5
Adhesive grammage	[g/m ²]	230
Peel resistance	[N/25 mm]	≥25
Application temperature	[°C]	+5 to +30
Temperature resistance	[°C]	-40 to +100
UV resistance	[month]	<4
Packaging	[roll]	12
Pallet	[box/roll]	60 / 720
Storage		In dry indoor areas, in original packaging.



Eurovent **TOPBAND**

Application: Used for bonding and repairing roof membranes, wind barrier membranes, and other polypropylene-based building products. Ideal for fixing various types of damage such as holes, cuts, or installation tears. Also adheres well to surfaces such as wood, brick, and smooth concrete.

Assembly: The application area must be structurally sound, dry, and free from dust and grease. Before bonding, the surfaces must be thoroughly cleaned and adhesion tests performed. Finished joints must not be exposed to standing water or constant mechanical load. Wrinkles and tension in the tape should be smoothed out.

Safety: The product is not intended for consumption. Avoid contact with eyes. In case of skin irritation, consult a doctor.

Storage / transport: The product should be stored at room temperature in dry, covered areas, free from moisture and direct UV exposure. It must be transported in covered vehicles and properly secured against damage. The product should be protected from exposure to chemical agents, especially solvent-based substances, as they may impair its technical performance or cause permanent damage.

The product is covered by a warranty, provided that all guidelines specified in the technical data sheet are strictly followed. The manufacturer reserves the right to reject warranty claims if these guidelines are not observed.

Contained information, advice and guidance is given based on our knowledge, researches, experience and in good faith. We are not responsible for the consequences of improper or incorrect use of our products. Each user of this material will ensure in every possible way, including an examination of the final product in the relevant conditions, the suitability of supplied materials to achieve the objectives pursued by him.

Product information can be found on the website: www.eurovent.de

Update date: 15/07/2025