


TECHNICAL DATA SHEET

Eurovent **ALUFIX**



Single-sided metallized tape designed for bonding and repairing aluminum foils and building components made of aluminum or coated with an aluminum layer. It is made of polyethylene film coated with aluminum and features a special adhesive based on acrylic dispersion.

PARAMETER	UNIT	VALUE
Material		PE foil, adhesive based on acrylic dispersion
Width	[mm]	50; 75
Length	[mb]	50
Thickness	[mm]	0,051
UV Resistance		resistance
Temperature resistance	[°C]	-30 to +90
Application temperature	[°C]	+5 to +40
Maximum tensile strength	[N/25 mm]	100
Elongation at break	[%]	140
Packaging	[roll]	50 mm: 36 75 mm: 24
Paleta	[roll]	50 mm: 3456 75 mm: 1728
Storage		In dry rooms, in original packaging



Eurovent ALUFIX

Application: Used for bonding and repairing vapour-permeable and vapour-barrier membranes made of aluminum or synthetic materials with a metallized surface. It also performs exceptionally well in repairing various types of damage, such as holes, cuts, or installation-related tears in building structure components.

Assembly: The application surface must be structurally sound, dry, and free from dust and grease. Before bonding, the surfaces should be thoroughly cleaned, and adhesion tests should be performed. Finished joints must not be exposed to standing water or continuous mechanical load. Wrinkles and tension in the tape should be smoothed out.

Safety: The product is not intended for consumption. Avoid contact with eyes. In case of skin irritation, consult a doctor.

Storage / transport: The product must be stored at room temperature in dry, covered areas that are free from moisture and direct UV radiation. It should be transported using covered vehicles and properly secured to prevent damage. The product must be protected from exposure to chemicals, especially solvent-based substances, as these may degrade its technical properties or cause permanent damage.

The product is covered by a warranty, provided that the guidelines outlined in the technical data sheet are strictly followed. The manufacturer reserves the right to reject any warranty claims if these guidelines are not adhered to.

Contained information, advice and guidance is given based on our knowledge, researches, experience and in good faith. We are not responsible for the consequences of improper or incorrect use of our products. Each user of this material will ensure in every possible way, including an examination of the final product in the relevant conditions, the suitability of supplied materials to achieve the objectives pursued by him.

The information on the product is included on the website: www.eurovent.de

Date of update: 04/02/2026